COMPONENT

Clip with gripper

Grid clip with integrated gripper: the cable is adjusted directly from the profile.

TECHNICAL DATA

Cable range	**Ø1.2 – 2.0 mm**
Body	**Ø10 × 32 mm**
Thread / fixing	**Base 35 × 54 mm**
Material	**Brass**
Finishes	**Nickel (NI) · black (BK) · white (WH)**
Working load	**14 – 37 kg**
Safety factor	**5:1**

INSTALLATION

1
Snap the clip onto the flange of the T grid profile.

2
Check that it is centred and fully seated.

3
Hang the cable or accessory. Do not exceed the grid load.

ORDER CODE

DS-T-G-NI/BK/WH

NI nickel · BK black · WH white

Part of: DS-T-24

WORKING LOAD PER CABLE

CABLE	GALVANISED	STAINLESS AISI 304
Ø1.2 mm	14 kg	13 kg
Ø1.5 mm	21 kg	20 kg
Ø2.0 mm	37 kg	34 kg

Static load with a 5:1 safety factor, based on 60 % of the cable break load (gripper efficiency). Theoretical values until laboratory validation.

DSUSPEND LABORATORY TESTS

Tensile test to failure	○ PENDING
Slip under load	○ PENDING
Salt spray ISO 9227	○ PENDING
Adjustment cycles	○ PENDING

SAFETY

Static loads only

No chlorine or corrosive areas

No grease or lubricants

Never use frayed cable

Maximum 60° inclination

Do not paint components

Provisional document: data will be completed with our laboratory tests. Images for reference only. Data subject to change without notice.